

ProVulc Vulcanising Machines List

The ProVulc Vulcanising Machines listed below includes 1 set of Vulcanising Platens, complete with a pressure bag, an aluminum bag plate, and water hoses, operating at 415 Volt, 3 Phase, 50 Hz. Each set also comes with an upgraded Water Pump, one P1 Electrical Control Box, and Aluminum Traverse Bars, complete with pressure bolt assemblies and safety restraining equipment.

Belt Width (mm)	Platens Dimensions (mm)		Bias Angle		Power (kW)	Aluminium Traverse Bars	
			Standard	Custom		Size (mm)	Quantity for 200 psi
800 Belt	950	x 680	17.3°	22°	8	1230x165x170	8
	950	x 850	17.3°	22°	9		10
	950	x 1010	17.3°	22°	11		12
1000 Belt	1160	x 680	17.3°	22°	10	1440x165x170	8
	1160	x 850	17.3°	22°	12		10
	1160	x 1010	17.3°	22°	14		12
1200 Belt	1380	x 680	17.3°	22°	11	1660x165x250	8
	1380	x 850	17.3°	22°	14		10
	1380	x 1010	17.3°	22°	17		12
1400 Belt	1600	x 680	17.3°	22°	13	1880x165x250	8
	1600	x 850	17.3°	22°	16		10
	1600	x 1010	17.3°	22°	19		12
1600 Belt	1900	x 680	17.3°	22°	13	2180x165x250	8
	1900	x 850	17.3°	22°	19		10
	1900	x 1010	17.3°	22°	23		12
1800 Belt	2100	x 680	17.3°	22°	17	2400x165x320	8
	2100	x 850	17.3°	22°	21		10
	2100	x 1010	17.3°	22°	25		12
2000 Belt	2300	x 680	17.3°	22°	18	2600x165x320	8
	2300	x 850	17.3°	22°	23		10
	2300	x 1010	17.3°	22°	28		12
2200 Belt	2500	x 680	17.3°	22°	21	2800x165x320	8
	2500	x 850	17.3°	22°	25		10
	2500	x 1010	17.3°	22°	30		12

